

MOVE IT 25 S track corner

050-731103G



Project / Type

Notes

Count / Date



48V

General

Ceiling , Suspended

gold , gold dust/RAL9005 ¹

Inner colour black

IP20

Electrical

DALI-2 single control

PC3 48V

Physical

length 637 mm

width 610 mm

height 31 mm

1 kg


¹ RAL code

Installation instructions



90° angle connector; Thin extruded aluminium profile with 31mm height and 28mm width groove; for wall-/ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with integrated power track profile for take off of supply voltage and DALI signal; surface gold; powder coated / anodised; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3 48V; accessories are listed separately;

Product drawing



[“050-731103G”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com