



Project / Type
Notes
Count / Date



RG0 IEC 62471	220-240V	no UV radiation	X-PERT
------------------	----------	-----------------	--------

<b>General</b>
Ceiling / Wall , Semi-Recessed <sup>1</sup> -Surface <sup>2</sup>
white , RAL9010 <sup>3</sup>
2010 lm/m
front IP40 <sup>1</sup> -IP20 <sup>2</sup> , back IP20
4900 lm
traffic white

<b>LED</b>
3000 K
CRI ≥ 80
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
MR 0.54
MDER 0.49


<b>Optical</b>
High Performance Opal
opal (lambertsch)
PstLM ≤ 1.0 <sup>4</sup>
SVM ≤ 0.4 <sup>4</sup>

Low profile recessed mounted luminaire, 15 mm visible height or low profile surface mounted luminaire, 28 mm total height; converter integrated into luminaire housing; suitable for wall or ceiling mounting; suitable for installation in primed or exposed concrete, in plasterboard constructions and in plastered walls or ceilings; for continuous lighting systems; surface white powder coated; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light directed downward through LGP (LIGHT GUIDING PRISM) body and high efficiency reflector; HPO (High Performance Opal) cover for uniform illumination; flush cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection from below IP40 (from above IP20); PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source not replaceable; control gear replaceable by an authorized professional;


<b>Electrical</b>
DALI-2
system 38 W
PC1 220-240V
system 129 lm/W <sup>5</sup>
1 DALI Addr.
16 W/m

<b>Physical</b>
length 2438 mm
width 89 mm
height 28 mm
5.5 kg

Light distribution



Product drawing



<b>Cutout</b>
length 2451 mm
width 70 mm
min. ceiling thickness 12.5 mm
recessed depth 13 mm

<sup>1</sup> semi-recessed <sup>2</sup> surface <sup>3</sup> RAL code  
<sup>4</sup> Value of containing product at full load (undimmed)  
<sup>5</sup> incl. optical losses and the efficiency of the operating device (converter)

Installation instructions





Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B13	24
B16	30
B20	37
C10	31
C13	40
C16	51
C20	62

Components

INSTALLATION CHANNEL

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
2438 mm	traffic white	2438-89-28	051-8920247



Mounting accessories

END CAPS

COLOUR	ARTICLE NUMBER(S)
pure white	051-8992217
jet black	051-8992218



Mounting accessories

LINEAR CONNECTOR

TYPE	ARTICLE NUMBER(S)
1 pair	051-8992110
10 pairs	051-8992110:10



POWER FEEDER CONNECTOR

ARTICLE NUMBER(S)
051-8992330



Other accessories

DISMOUNTING TOOL

TYPE	ARTICLE NUMBER(S)
vacuum cup	086-30000

