

MOVE IT 45 track indirect

050-7432518



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL9005 ¹

1330 lm/m

IP20

648 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.61

MDER 0.55

Electrical

non DIM

6.2 W

PC3 48V

105 lm/W

13 W/m

Physical

length 620 mm


width 48 mm

height 60 mm


0.8 kg

Extruded aluminium profile with 45mm width groove; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; indirect light component covered with opal lens cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power rail profile for supply voltage feed; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3 48V; accessories are listed separately; light source not replaceable;

Light distribution



Product drawing



¹ RAL code

Installation instructions



Lighting calculator

