

# MICROPRISMATIC UGR < 22

MOVE IT 45  
050-3242538P



Project / Type	
Notes	
Count / Date	



### General

Ceiling / Wall , Track	
black , RAL 9005 <sup>1</sup>	
IP20	
1490 lm	
optical inset 84 lm/W <sup>2</sup>	

### LED

3000 K	
CRI ≥ 90	
L85 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>f(1-15)</sub> : 89	
MR 0.61	
MDER 0.55	

### Optical

Microprismatic	
microprismatic	
PstLM ≤ 1.0 <sup>3</sup>	
SVM ≤ 0.4 <sup>3</sup>	


### Electrical

DALI-2 single control	
48 V	
fixture 25.4 W	
fixture 59 lm/W <sup>4</sup>	
optical inset 17.8 W	
PC3	
1 DALI Addr.	

### Physical

length 605 mm	
width 43 mm	
height 48 mm	
0.62 kg	

### Light distribution



### Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses  
<sup>3</sup> Value of containing product at full load (undimmed)  
<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

### Installation instructions

