

# TULA micro suspended

MOVE IT 25 / 25 S / 45

050-1815414F



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Suspended \_\_\_\_\_

chrome \_\_\_\_\_

IP20 \_\_\_\_\_

1040 lm \_\_\_\_\_

optical inset 87 lm/W<sup>1</sup> \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 96 , R<sub>r</sub>: 90 , R<sub>t(1-15)</sub>: 88 \_\_\_\_\_

MR 0.55 \_\_\_\_\_

MDER 0.5 \_\_\_\_\_

## Optical

flood \_\_\_\_\_

beam angle 44° \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrical

non DIM \_\_\_\_\_

48 V \_\_\_\_\_

fixture 14.1 W \_\_\_\_\_

optical inset 12.0 W \_\_\_\_\_

PC3 \_\_\_\_\_

## Physical

diameter 47 mm \_\_\_\_\_


height 500 mm \_\_\_\_\_

0.7 kg \_\_\_\_\_

2000 mm with hook \_\_\_\_\_

<sup>1</sup> incl. consideration of optical losses  
<sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



flood 44°

h (m)	E0° (lx)	ø (m)
1	1930	0.82
2	480	1.64
3	210	2.45
4	120	3.27
5	80	4.09

## Product drawing



## Installation instructions

## Lighting calculator

