

TULA nano suspended

MOVE IT 25 / 25 S / 45

050-1811537F



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

white , RAL 9016 ¹

IP20

707 lm

optical inset 78 lm/W²

LED

3000 K

CRI \geq 90

initial MacAdam \leq 3 SDCM

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88

MR 0.59

MDER 0.53

Optical

flood

beam angle 30°

PstLM \leq 1.0 ³

SVM \leq 0.4 ³

Electrical

DALI-2

48 V

fixture 12.1 W

fixture 58 lm/W⁴

optical inset 9.1 W

PC3

1 DALI Addr.

Physical

diameter 26 mm

height 500 mm

0.35 kg


2000 mm with hook

¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses


³ Value of containing product at full load (undimmed)

⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.



Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



flood 30°

h (m)	E0° (lx)	ø (m)
1	2080	0.53
2	520	1.07
3	230	1.60
4	130	2.13
5	80	2.66

Product drawing



Installation instructions



Lighting calculator

