

# MOVE IT 25 trimless track corner


050-7201018



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Recessed

black , RAL9005 <sup>1</sup>

IP20

Electrical

non DIM

PC3 48V

Physical

length 672 mm

width 645 mm

height 60 mm

1.95 kg


<sup>1</sup> RAL code

Installation instructions



90° angle connector; Extruded aluminium profile with 28mm width groove; for trimless installation in plasterboard ceilings; suitable for wall or ceiling mounting; suitable for ceiling thickness of 12.5 mm; with integrated power rail profile for supply voltage feed; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3 48V; accessories are listed separately;

Product drawing



[“050-7201018”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)



Project / Type

Notes

Count / Date

Electrical accessories

DALI-2 SELV DEVICE

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
control unit	212-37-26	050-2061130

