

TULA nano suspended

MOVE IT 25 / 25 S / 45

050-1711418F



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

black , RAL 9005 ¹

IP20

667 lm

optical inset 73 lm/W²

LED

2700 K

CRI \geq 90

L80 / 50000 h

initial MacAdam \leq 2 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.53

MDER 0.48

Optical

flood

beam angle 30°

PstLM \leq 1.0 ³

SVM \leq 0.4 ³

Electrical

non DIM

48 V

fixture 12.1 W

fixture 55 lm/W⁴

optical inset 9.1 W

PC3

Physical

diameter 26 mm

height 500 mm

0.35 kg

1500 mm


¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses

³ Value of containing product at full load (undimmed)

⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.


Light distribution



flood 30°

h (m)	E0° (lx)	ø (m)
1	1960	0.53
2	490	1.07
3	220	1.60
4	120	2.13
5	80	2.66

Product drawing



Installation instructions



Lighting calculator

