

# PAL cable 120mm suspended

MOVE IT 25 / 25 S / 45

050-161353X



Project / Type

Notes

Count / Date



## General

Ceiling , Track Suspended

special colours

IP20

501 lm

optical inset 73 lm/W<sup>1</sup>

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

## Optical

opal (lambertsch)

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

48 V

fixture 9.1 W

fixture 55 lm/W<sup>3</sup>

optical inset 6.8 W

PC3

1 DALI Addr.

## Physical

cable 2000 mm with hook

diameter 120 mm

height 120 mm


0.4 kg

<sup>1</sup> OPTICAL INSET: incl. consideration of optical losses

<sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Light distribution



## Product drawing

