

TULA micro suspended

MOVE IT 25 / 25 S / 45

050-1715D34F



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

chrome

IP20

290 lm

LED

tunable white

2200 K - 4000 K

CRI \geq 90

L95 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 88

MR 0.83

MDER 0.75

Optical

flood

beam angle 46°

PstLM \leq 1.0 ¹

SVM \leq 0.4 ¹

Electrical

DALI-2 DT8

system 5.4 W

PC3

system 54 lm/W²

Physical

diameter 47 mm


height 500 mm

0.65 kg

1500 mm

Decorative pendant light inset made of aluminium; surface polished chrome; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; light colour: tunable white diodes (2200-4000 K); binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 46° beam; degree of protection IP20; PC3; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



flood 46°

h (m)	EO° (lx)	ø (m)
1	467	0.86
2	117	1.71
3	52	2.57
4	29	3.43
5	19	4.28

Product drawing



¹ Value of containing product at full load (undimmed)

² incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

