

TULA micro suspended

MOVE IT 25 / 25 S / 45

050-1815534F



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

chrome

IP20

1090 lm

optical inset 91 lm/W¹

LED

3000 K

CRI \geq 90

L80 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 98 , R_r: 91 , R_{t(1-15)}: 89

MR 0.62

MDER 0.56

Optical

flood

beam angle 44°

PstLM \leq 1.0 ²

SVM \leq 0.4 ²

Electrical

DALI-2

48 V

fixture 14.1 W

fixture 77 lm/W³

optical inset 12.0 W

PC3

1 DALI Addr.

Physical

diameter 47 mm

height 500 mm

0.7 kg


2000 mm with hook

¹ OPTICAL INSET: incl. consideration of optical losses

² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



| flood 44° | | |
|-----------|----------|-------|
| h (m) | E0° (lx) | ø (m) |
| 1 | 2020 | 0.82 |
| 2 | 510 | 1.64 |
| 3 | 220 | 2.45 |
| 4 | 130 | 3.27 |
| 5 | 80 | 4.09 |

Product drawing



Installation instructions



Lighting calculator

