

TULA micro suspended

MOVE IT 25 / 25 S / 45

050-181551XF



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; surface special colours powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC3; non-dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

III

X-PERT

UGR
 ≤ 19

cd/m²
 ≤ 1500

CRI
 ≥ 90

X-PERT

General

Ceiling , Suspended

special colours

IP20

1090 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 98 , R_f: 91 , R_{1-15}: 89

MR 0.62

MDER 0.56

Optical

flood

beam angle 44°

Electrical

non DIM

14.1 W

PC3

77 lm/W

Physical


diameter 47 mm

height 500 mm

0.7 kg

2000 mm with hook

Light distribution



flood 44°

h (m)	E0° (lx)	ø (m)
1	2020	0.82
2	510	1.64
3	220	2.45
4	130	3.27
5	80	4.09

Product drawing



Installation instructions



Lighting calculator

