

TULA nano suspended

MOVE IT 25 / 25 S / 45

050-1711537F



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

white , RAL 9016 ¹

IP20

707 lm

optical inset 78 lm/W²

LED

3000 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

R_g: 100 , R_f: 91 , R_{f(1-15)}: 88

MR 0.59

MDER 0.53

Optical

flood

beam angle 30°

PstLM ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrical

DALI-2

48 V

fixture 12.1 W

fixture 58 lm/W⁴

optical inset 9.1 W

PC3

1 DALI Addr.

Physical


diameter 26 mm

height 500 mm

0.35 kg

1500 mm


Light distribution



flood 30°

h (m)	E0° (lx)	ø (m)
1	2080	0.53
2	520	1.07
3	230	1.60
4	130	2.13
5	80	2.66

Product drawing



¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses

³ Value of containing product at full load (undimmed)

⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

