

ARY adjustable rod suspended

MOVE IT 25 / 25 S / 45
050-063141XF



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

tilt max 90° _____

rotation 265° _____

special colours _____

IP20 _____

1040 lm _____

LED

2700 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 96 , R_f: 90 , R₍₁₋₁₅₎: 88 _____

MR 0.55 _____

MDER 0.5 _____

Optical

flood _____

beam angle 44° _____

Electrical

non DIM _____

14.1 W _____

PC3 48V _____

74 lm/W _____

Physical

rod 1500 mm with hook _____


diameter 47 mm _____

height 110 mm _____

0.5 kg _____


Decorative pendant light inset made of aluminium; surface special colours powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (special colours) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (special colours) for multiple positioning of the luminaire in the room; spotlight head 265° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC3 48V; non-dimmable; light source not replaceable;

Light distribution



flood 44°			
h (m)	EO° (lx)	ø (m)	
1	1930	0.82	
2	480	1.64	
3	210	2.45	
4	120	3.27	
5	80	4.09	

Product drawing



Installation instructions



Lighting calculator

