

ARY adjustable rod suspended


MOVE IT 25 / 25 S / 45
050-0531518M



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

tilt max 90° _____

rotation 265° _____

black , RAL9005 ¹ _____

IP20 _____

1020 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 98 , R_f: 91 , R₍₁₋₁₅₎: 89 _____

MR 0.62 _____

MDER 0.56 _____

Optical

medium _____

beam angle 25° _____

Electrical

non DIM _____

14.1 W _____

PC3 48V _____

72 lm/W _____

Physical

rod 1500 mm _____


diameter 47 mm _____

height 110 mm _____

0.45 kg _____


Decorative pendant light inset made of aluminium; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (black) 1500mm, feed in U-profile; spotlight head 265° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC3 48V; non-dimmable; light source not replaceable;

Light distribution



medium 25°		
h (m)	EO° (lx)	ø (m)
1	4410	0.44
2	1100	0.89
3	490	1.33
4	280	1.78
5	180	2.22

Product drawing



¹ RAL code

Installation instructions



Lighting calculator

