

# ARY adjustable rod suspended

MOVE IT 25 / 25 S / 45  
050-0631D38M



Project / Type \_\_\_\_\_  
Notes \_\_\_\_\_  
Count / Date \_\_\_\_\_



## General

Ceiling , Track Suspended  
tilt max 90°  
rotation 265°  
black , RAL 9005 <sup>1</sup>  
IP20  
269 lm  
optical inset 67 lm/W<sup>2</sup>

## LED

tunable white  
2200 K - 4000 K  
CRI ≥ 90  
L95 / 50000 h  
initial MacAdam ≤ 3 SDCM  
MR 0.4  
MDER 0.37

## Optical

medium  
beam angle 21°  
PstLM ≤ 1.0 <sup>3</sup>  
SVM ≤ 0.4 <sup>3</sup>

## Electrical

DALI-2 DT8  
48 V  
fixture 5.4 W  
optical inset 4.0 W  
PC3  
1 DALI Addr.


## Physical

rod 1500 mm with hook  
diameter 47 mm  
height 110 mm  
0.5 kg

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses  
<sup>3</sup> Value of containing product at full load (undimmed)

Decorative pendant light inset made of aluminium; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (black) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; spotlight head 265° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; light colour: tunable white diodes (2200-4000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 21° beam; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;


## Light distribution



medium 21°

h (m)	E0° (lx)	ø (m)
1	1370	0.38
2	340	0.76
3	150	1.14
4	90	1.52
5	50	1.90

## Product drawing



## Installation instructions



## Lighting calculator

