

ARY cable suspended

MOVE IT 25 / 25 S / 45

050-0611D3XM



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling , Track Suspended _____
 special colours _____
 IP20 _____
 269 lm _____
 optical inset 67 lm/W¹ _____

LED

tunable white _____
 2200 K - 4000 K _____
 CRI ≥ 90 _____
 L95 / 50000 h _____
 initial MacAdam ≤ 3 SDCM _____
 MR 0.4 _____
 MDER 0.37 _____

Optical

medium _____
 beam angle 21° _____
 PstLM ≤ 1.0² _____
 SVM ≤ 0.4² _____

Electrical


DALI-2 DT8 _____
 48 V _____
 fixture 5.4 W _____
 fixture 50 lm/W³ _____
 optical inset 4.0 W _____
 PC3 _____
 1 DALI Addr. _____

Physical

cable 2000 mm with hook _____
 diameter 47 mm _____
 height 110 mm _____
 0.4 kg _____

Decorative pendant light inset made of aluminium; surface special colours powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 2000mm suspension, incl. feed (special colours), can be individually shortened, incl. ceiling mounting ring + hook (special colours) for multiple positioning of the luminaire in the room; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; light colour: tunable white diodes (2200-4000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 21° beam; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;


Light distribution



medium 21°

h (m)	E0° (lx)	ø (m)
1	1370	0.38
2	340	0.76
3	150	1.14
4	90	1.52
5	50	1.90

Product drawing



¹ OPTICAL INSET: incl. consideration of optical losses

² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

