

TULA nano suspended

MOVE IT 25 / 25 S / 45

050-081141XM



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

special colours

IP20

691 lm

optical inset 76 lm/W¹

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89

MR 0.53

MDER 0.48

Optical

medium

beam angle 24°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

48 V

fixture 12.1 W

fixture 57 lm/W³

optical inset 9.1 W

PC3

Physical


diameter 26 mm

height 300 mm

1.1 kg

2000 mm with hook

Light distribution



medium 24°

h (m)	EO° (lx)	ø (m)
1	2820	0.43
2	700	0.85
3	310	1.28
4	180	1.71
5	110	2.13

Product drawing



¹ OPTICAL INSET: incl. consideration of optical losses

² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

