

# ARY cable suspended

MOVE IT 25 / 25 S / 45  
050-0611637M



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

white , RAL9016 <sup>1</sup>

IP20

1090 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 96 , R<sub>f</sub>: 89 , R<sub>(1-5)</sub>: 89

MR 0.84

MDER 0.76

Optical

medium

beam angle 25°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

Electrical

DALI-2

system 14.1 W

PC3 48V

system 77 lm/W<sup>3</sup>

1 DALI Addr.

Physical

cable 2000 mm with hook


diameter 47 mm

height 110 mm

0.4 kg


Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 2000mm suspension, incl. feed (white), can be individually shortened, incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

## Light distribution



| medium 25° |          |       |
|------------|----------|-------|
| h (m)      | E0° (lx) | ø (m) |
| 1          | 4710     | 0.44  |
| 2          | 1180     | 0.89  |
| 3          | 520      | 1.33  |
| 4          | 290      | 1.78  |
| 5          | 190      | 2.22  |

## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

## Installation instructions



## Lighting calculator



# ARY cable suspended

MOVE IT 25 / 25 S / 45

050-0611637M



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF               | 0.98   | 0.97   | 0.96   | 0.95   | 0.94   |
| LSF                | 1      | 1      | 1      | 1      | 1      |

|                  |                              |                   |                                 |
|------------------|------------------------------|-------------------|---------------------------------|
| MF               | LMF × RSMF × LLMF × LSF      | RSMF <sup>a</sup> | Room Surface Maintenance Factor |
| MF               | Maintenance Factor           | LLMF              | Lamp Lumens Maintenance Factor  |
| LMF <sup>a</sup> | Luminaire Maintenance Factor | LSF               | Lamp Survival Faktor            |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Mounting accessories

### RING TRACK MOUNTED

| COLOUR        | Ø (MM) | ARTICLE NUMBER(S) |
|---------------|--------|-------------------|
| traffic white | 50     | 050-0510117       |
| jet black     | 50     | 050-0510118       |



### RING CEILING MOUNTED

| COLOUR        | Ø (MM) | ARTICLE NUMBER(S) |
|---------------|--------|-------------------|
| traffic white | 50     | 050-0510217       |
| jet black     | 50     | 050-0510218       |



## Optical accessories

### SHADE 300

| COLOUR           | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black     | 300    | 049-593311B       |
| velvet beige     | 300    | 049-593311C       |
| woodpecker olive | 300    | 049-593311G       |
| kingfisher grey  | 300    | 049-593311L       |
| madeira brown    | 300    | 049-593311T       |
| signal white     | 300    | 049-593311W       |



### SHADE 400

| COLOUR           | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black     | 400    | 049-593411B       |
| velvet beige     | 400    | 049-593411C       |
| woodpecker olive | 400    | 049-593411G       |
| kingfisher grey  | 400    | 049-593411L       |
| madeira brown    | 400    | 049-593411T       |
| signal white     | 400    | 049-593411W       |



### SHADE 500

| COLOUR           | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black     | 500    | 049-593511B       |
| velvet beige     | 500    | 049-593511C       |
| woodpecker olive | 500    | 049-593511G       |
| kingfisher grey  | 500    | 049-593511L       |
| madeira brown    | 500    | 049-593511T       |
| signal white     | 500    | 049-593511W       |



["050-0611637M"] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

03.12.2024

# ARY cable suspended

MOVE IT 25 / 25 S / 45  
050-0611637M



Project / Type

Notes

Count / Date

## Optical accessories

### OVAL LENS

|        |                   |
|--------|-------------------|
| Ø (MM) | ARTICLE NUMBER(S) |
| 42     | 007-1965880       |



### SOFT LENS

|        |                   |
|--------|-------------------|
| Ø (MM) | ARTICLE NUMBER(S) |
| 42     | 007-1965980       |



### WALLWASHER LENS

|        |                   |
|--------|-------------------|
| Ø (MM) | ARTICLE NUMBER(S) |
| 42     | 007-1965780       |

