

ARY rod suspended

MOVE IT 25 / 25 S / 45

050-052163XF



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

special colours

IP20

1170 lm

optical inset 97 lm/W¹

LED

4000 K

CRI \geq 90

L90 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 96 , R_r: 89 , R_{t(1-15)}: 89

MR 0.84

MDER 0.76

Optical

flood

beam angle 44°

PstLM \leq 1.0 ²

SVM \leq 0.4 ²

Electrical

DALI-2

48 V

fixture 14.1 W

fixture 83 lm/W³

optical inset 12.0 W

PC3

1 DALI Addr.

Physical

rod 1500 mm

diameter 47 mm

height 110 mm


0.45 kg

¹ OPTICAL INSET: incl. consideration of optical losses

² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



flood 44°

h (m)	EO ² (lx)	ø (m)
1	2170	0.82
2	540	1.64
3	240	2.45
4	140	3.27
5	90	4.09

Product drawing



Installation instructions



Lighting calculator

