

# WALLWASHER FLUSH

MOVE IT 25

050-0211438A




Project / Type	
Notes	
Count / Date	




Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; with specially computed, asymmetric lens for homogeneous vertical lighting intensity; optical attachment available as accessory; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

## Light distribution



## Product drawing



## General

Ceiling / Wall , Track	
black , RAL 9005 <sup>1</sup>	
IP20	
415 lm	
optical inset 106 lm/W <sup>2</sup>	

## LED

2700 K	
CRI $\geq 90$	
L80 / 50000 h	
initial MacAdam $\leq 3$ SDCM	
R <sub>g</sub> : 95 , R <sub>r</sub> : 92 , R <sub>t(1-15)</sub> : 90	
MR 0.45	
MDER 0.41	

## Optical

wallwasher	
PstLM $\leq 1.0$ <sup>3</sup>	
SVM $\leq 0.4$ <sup>3</sup>	

## Electrical

DALI-2 single control	
48 V	
fixture 5.6 W	
fixture 74 lm/W <sup>4</sup>	
optical inset 3.9 W	
PC3	
1 DALI Addr.	

## Physical

length 305 mm	
width 25 mm	
height 45 mm	
0.23 kg	

<sup>1</sup> RAL code  
<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses  
<sup>3</sup> Value of containing product at full load (undimmed)  
<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Installation instructions

