

# ARY rod suspended

MOVE IT 25 / 25 S / 45


050-052141XM



Project / Type

Notes

Count / Date



## General

Ceiling , Track Suspended

special colours

IP20

972 lm

optical inset 81 lm/W<sup>1</sup>

## LED

2700 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 96 , R<sub>r</sub>: 90 , R<sub>t(1-15)</sub>: 88

MR 0.55

MDER 0.5

## Optical

medium

beam angle 25°

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Electrical

non DIM

48 V

fixture 14.1 W

fixture 69 lm/W<sup>3</sup>

optical inset 12.0 W

PC3

## Physical

rod 1500 mm

diameter 47 mm

height 110 mm


0.45 kg

<sup>1</sup> OPTICAL INSET: incl. consideration of optical losses

<sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	4200	0.44
2	1050	0.89
3	470	1.33
4	260	1.78
5	170	2.22

## Product drawing



## Installation instructions



## Lighting calculator

