

w201 Extra small pendant s2 suspended

MOVE IT 25 / 25 S / 45 with hook
050-0462418



Project / Type _____

Notes _____

Count / Date _____



Decorative pendant light inset made of aluminium; cone-shaped shade; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3500mm suspension, incl. feed (black), can be individually shortened, incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; non-dimmable; light source not replaceable; control gear replaceable by an authorized professional;



General

Ceiling , Suspended
black , RAL 9005 ¹
IP20
520 lm

LED

2700 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM

Optical

flood
beam angle 91°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Electrical

non DIM
48 V
system 7.9 W
PC3
system 66 lm/W³

Physical

diameter 91 mm
height 94 mm
0.6 kg


Light distribution



flood 91°

h (m)	EO° (lx)	ø (m)
1	246	2.02
2	61	4.04
3	27	6.07
4	15	8.09
5	10	10.11

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

