

JUST 45 MOVE IT 25 / 25 S / 45

050-0131E3XF



Project / Type


Notes

Count / Date



Cylindrical spotlight in aluminium; surface special colours powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; CWD (Colour Warm Dimming) of 2000K - 3000K; binning initial MacAdam ≤ 4 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 42° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; with colour warm dimming a step-less change of colour temperature occurs simultaneously with a reduction in light intensity; similar to the dimming characteristic of an incandescent lamp; reducing the illuminance enables a very warm tone; light source not replaceable;


Light distribution



flood 42°

h (m)	E0° (lx)	ø (m)
1	870	0.77
2	218	1.55
3	97	2.32
4	54	3.10
5	35	3.87

Product drawing



General

Ceiling / Wall , Track

tilt max 90°

rotation 360°

special colours

IP20

434 lm

LED

colour warm dimming

2000 K - 3000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 4 SDCM

R_g: 100 , R_f: 91 , R_{f(1-5)}: 90

MR 0.61

MDER 0.55

Optical

flood

beam angle 42°

Electrical

DALI-2 single control

11.5 W

PC3 48V

38 lm/W

1 DALI Addr.

Physical

diameter 45 mm

height 68 mm

0.2 kg

Installation instructions

