

ARY cable suspended

MOVE IT 25 / 25 S / 45

050-051163XF



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; surface special colours powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (special colours), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;



General

Ceiling , Track Suspended

special colours

IP20

1170 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 , R_f: 89 , R₍₁₋₁₅₎: 89

MR 0.84

MDER 0.76

Optical

flood

beam angle 44°

Electrical

DALI-2

14.1 W

PC3 48V

83 lm/W

1 DALI Addr.

Physical


cable 1500 mm

diameter 47 mm

height 110 mm


0.35 kg

Light distribution



| flood 44° | | |
|-----------|----------|-------|
| h (m) | E0° (lx) | ø (m) |
| 1 | 2170 | 0.82 |
| 2 | 540 | 1.64 |
| 3 | 240 | 2.45 |
| 4 | 140 | 3.27 |
| 5 | 90 | 4.09 |

Product drawing



Installation instructions



Lighting calculator



ARY cable suspended

MOVE IT 25 / 25 S / 45

050-051163XF



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF | 0.98 | 0.97 | 0.96 | 0.95 | 0.94 |
| LSF | 1 | 1 | 1 | 1 | 1 |

| | | | |
|------------------|------------------------------|-------------------|---------------------------------|
| MF | LMF × RSMF × LLMF × LSF | RSMF ^a | Room Surface Maintenance Factor |
| MF | Maintenance Factor | LLMF | Lamp Lumens Maintenance Factor |
| LMF ^a | Luminaire Maintenance Factor | LSF | Lamp Survival Faktor |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

RING TRACK MOUNTED

| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|---------------|--------|-------------------|
| traffic white | 50 | 050-0510117 |
| jet black | 50 | 050-0510118 |



RING CEILING MOUNTED

| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|---------------|--------|-------------------|
| traffic white | 50 | 050-0510217 |
| jet black | 50 | 050-0510218 |



Optical accessories

SHADE 300

| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black | 300 | 049-593311B |
| velvet beige | 300 | 049-593311C |
| woodpecker olive | 300 | 049-593311G |
| kingfisher grey | 300 | 049-593311L |
| madeira brown | 300 | 049-593311T |
| signal white | 300 | 049-593311W |



SHADE 400

| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black | 400 | 049-593411B |
| velvet beige | 400 | 049-593411C |
| woodpecker olive | 400 | 049-593411G |
| kingfisher grey | 400 | 049-593411L |
| madeira brown | 400 | 049-593411T |
| signal white | 400 | 049-593411W |



SHADE 500

| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black | 500 | 049-593511B |
| velvet beige | 500 | 049-593511C |
| woodpecker olive | 500 | 049-593511G |
| kingfisher grey | 500 | 049-593511L |
| madeira brown | 500 | 049-593511T |
| signal white | 500 | 049-593511W |



[050-051163XF] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

22.07.2024