

# JUST 45 MOVE IT 25 / 25 S / 45

050-0131D38F



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

tilt max 90°

rotation 360°

black , RAL9005 <sup>1</sup>

IP20

674 lm

LED

tunable white

2700 K - 6500 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 97 , R<sub>r</sub>: 88 , R<sub>(1-15)</sub>: 88

MR 1.15

MDER 1.04

Optical

flood

beam angle 42°

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

Electrical

DALI-2 DT8 single control

system 11.3 W

PC3 48V

system 60 lm/W<sup>3</sup>

1 DALI Addr.

Physical

diameter 45 mm


height 68 mm

0.2 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)


Light distribution



flood 42°

h (m)	E0° (lx)	ø (m)
1	1350	0.77
2	340	1.55
3	150	2.32
4	80	3.10
5	50	3.87

Product drawing



Installation instructions



# JUST 45 MOVE IT 25 / 25

## S / 45

050-0131D38F



Project / Type

Notes

Count / Date

### Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

### Optical accessories

#### HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	42	007-1965188

