

JUST 45 MOVE IT 25 / 25 S / 45

050-0131D38F



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Track _____

tilt max 90° _____

rotation 360° _____

black , RAL9005 ¹ _____

IP20 _____

674 lm _____

LED

tunable white _____

2700 K - 6500 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 97 , R_r: 88 , R₍₁₋₁₅₎: 88 _____

MR 1.15 _____

MDER 1.04 _____

Optical

flood _____

beam angle 42° _____

P_{stLM} ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 DT8 single control _____

system 11.3 W _____

PC3 48V _____

system 60 lm/W³ _____

1 DALI Addr. _____

Physical


diameter 45 mm _____

height 68 mm _____

0.2 kg _____

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)


Light distribution



flood 42°

h (m)	E0° (lx)	ø (m)
1	1350	0.77
2	340	1.55
3	150	2.32
4	80	3.10
5	50	3.87

Product drawing



Installation instructions

