

JUST 45 MOVE IT 25 / 25 S / 45

050-0131D37M



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

tilt max 90°

rotation 360°

white , RAL9016 ¹

IP20

605 lm

LED

tunable white

2700 K - 6500 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 97 , R_r: 88 , R₍₁₋₁₅₎: 88

MR 1.15

MDER 1.04

Optical

medium

beam angle 21°

P_{stLM} ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2 DT8 single control

system 11.3 W

PC3 48V

system 54 lm/W³

1 DALI Addr.

Physical

diameter 45 mm


height 68 mm

0.2 kg

¹ RAL code ² Value of containing product at full load (undimmed)

³ incl. optical losses and the efficiency of the operating device (converter)


Light distribution



medium 21°

h (m)	E0° (lx)	ø (m)
1	3100	0.38
2	770	0.76
3	340	1.14
4	190	1.52
5	120	1.90

Product drawing



Installation instructions



[‘050-0131D37M’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com