

# PIVOT MOVE IT 25 / 25 S / 45 suspended

050-0322L380



Project / Type

Notes

Count / Date



### General

Ceiling , Track Suspended

rotation 360°

black , RAL9005 <sup>1</sup>

650 lm

Beam Angle Correspondence Sphere (360°)

Sorgente luminosa non direzionale

IP20

650 lm

Chromaticity Coordinate X: 0.388

Chromaticity Coordinate Y: 0.382

### LED

tunable white

1800 K - 4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.66

### Optical

opal (lambertsch)

### Electrical

DALI-2 DT8

5.3 W

PC3 48V

123 lm/W

1 DALI Addr.

### Physical

length 610 mm


width 33 mm

height 33 mm


0.35 kg

<sup>1</sup> RAL code

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator



# PIVOT MOVE IT 25 / 25 S / 45 suspended

050-0322L38O



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.9	0.9
LSF	1	1	1	1	1

MF

MF

LMF<sup>a</sup>

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF<sup>a</sup>

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

