

# PIVOT MOVE IT 25 / 25 S / 45 suspended

050-03224380



Project / Type

Notes

Count / Date



## General

Ceiling , Track Suspended

rotation 360°

black , RAL 9005 <sup>1</sup>

IP20

1190 lm

1980 lm/m

optical inset 161 lm/W<sup>2</sup>

## LED

2700 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.47

MDER 0.42

## Optical

opal (lambertsch)

PstLM ≤ 1.0 <sup>3</sup>

SVM ≤ 0.4 <sup>3</sup>

## Electrical

DALI-2

48 V

fixture 10.6 W

fixture 112 lm/W<sup>4</sup>

optical inset 7.4 W

PC3

1 DALI Addr.

18 W/m

## Physical

length 610 mm

width 33 mm

height 33 mm

0.35 kg


<sup>1</sup> RAL code

<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses


<sup>3</sup> Value of containing product at full load (undimmed)

<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

