

PIVOT MOVE IT 25 / 25 S / 45 suspended

050-03224380



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

rotation 360°

black , RAL 9005 ¹

IP20

1190 lm

1980 lm/m

optical inset 161 lm/W²

LED

2700 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.47

MDER 0.42

Optical

opal (lambertsch)

PstLM ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrical

DALI-2

48 V

fixture 10.6 W

fixture 112 lm/W⁴

optical inset 7.4 W

PC3

1 DALI Addr.

18 W/m

Physical

length 610 mm

width 33 mm

height 33 mm

0.35 kg


¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses


³ Value of containing product at full load (undimmed)

⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



Product drawing



Installation instructions



Lighting calculator



PIVOT MOVE IT 25 / 25 S / 45 suspended

050-03224380



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

