

MOUNTING HOUSING

600 trimless linear

049-8846038



Project / Type	
Notes	
Count / Date	



General

Ceiling , Recessed
jet black , RAL 9005 ¹
IP20

Electrical

DALI-2
PC1 220-240V
2 DALI Addr.

Physical

length 608 mm
width 269 mm
height 120 mm


Cutout

length 608 mm
width 136 mm
min. ceiling thickness 12.5 mm
max. ceiling thickness 12.5 mm
recessed depth 175 mm

Installation housing in pressed steel sheet with rectangular cut-out; for trimless installation in plasterboard ceilings; special edge design with perforations for better adhesion of filler; suitable for ceiling thickness of 12.5 mm; 6 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface jet black powder coated; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

¹ RAL code

Product drawing



Installation instructions



[‘049-8846038’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com