

# JUST 55

MOVE IT 25 / 25 S / 45

050-0142638F



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Track \_\_\_\_\_  
 tilt max 90° \_\_\_\_\_  
 rotation 360° \_\_\_\_\_  
 black , RAL9005 <sup>1</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 1880 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L80 / 50000 h \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_  
 R<sub>g</sub>: 96 , R<sub>f</sub>: 89 , R<sub>(f-15)</sub>: 89 \_\_\_\_\_  
 MR 0.84 \_\_\_\_\_  
 MDER 0.76 \_\_\_\_\_

## Optical

flood \_\_\_\_\_  
 beam angle 38° \_\_\_\_\_

## Electrical


DALI-2 single control \_\_\_\_\_  
 25.4 W \_\_\_\_\_  
 PC3 48V \_\_\_\_\_  
 74 lm/W<sup>2</sup> \_\_\_\_\_  
 1 DALI Addr. \_\_\_\_\_

## Physical

diameter 55 mm \_\_\_\_\_  
 height 100 mm \_\_\_\_\_  
 0.3 kg \_\_\_\_\_

Cylindrical spotlight in aluminium; surface black powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 38° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; light source not replaceable;


## Light distribution



flood 38°

h (m)	E0° (lx)	ø (m)
1	4680	0.69
2	1170	1.38
3	520	2.06
4	290	2.75
5	190	3.44

## Product drawing



<sup>1</sup> RAL code

<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)

## Installation instructions



## Lighting calculator



# JUST 55

MOVE IT 25 / 25 S / 45

050-0142638F



Project / Type

Notes

Count / Date

## Optical accessories

### HONEYCOMB LOUVER

COLOUR  
jet black

Ø (MM)  
50

ARTICLE NUMBER(S)  
007-1965598

