

JUST 45 MOVE IT 25 / 25 S / 45


050-013153XM



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track _____
 tilt max 90° _____
 rotation 360° _____
 special colours _____
 IP20 _____
 753 lm _____

LED

3000 K _____
 CRI ≥ 90 _____
 L85 / 50000 h _____
 initial MacAdam ≤ 3 SDCM _____
 R_g: 98 , R_f: 91 , R₍₁₋₁₅₎: 89 _____
 MR 0.62 _____
 MDER 0.56 _____

Optical

medium _____
 beam angle 23° _____

Electrical


DALI-2 single control _____
 11.2 W _____
 PC3 48V _____
 67 lm/W _____
 1 DALI Addr. _____

Physical

diameter 45 mm _____
 height 68 mm _____
 0.2 kg _____

Cylindrical spotlight in aluminium; surface special colours powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 23° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; light source not replaceable;


Light distribution



medium 23°

h (m)	E0° (lx)	ø (m)
1	3790	0.40
2	950	0.81
3	420	1.21
4	240	1.62
5	150	2.02

Product drawing



Installation instructions



Lighting calculator

