

MOUNTING HOUSING

square

049-8813038



Project / Type _____


Notes _____

Count / Date _____



Recessed housing made of pressed steel sheet for flush installation in plasterboard ceilings, underside of aluminium-reinforced plaster (paintable); with square cut-out; no break-out of edges; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 8-25 mm; 3 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface jet black powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

Product drawing



General

Ceiling , Recessed _____

jet black , RAL 9005 ¹ _____

IP20 _____

Electrical

DALI-2 _____

220-240 V _____

PC1 _____

1 DALI Addr. _____

PC2 _____

25 W _____

Dim DALI, Push Dim, Dim DSI, Dim Dali 2 _____

min 198 V _____

max 264 V _____

Constant Current _____

min 50 Hz _____

max 60 Hz _____

Physical

length 260 mm _____

width 260 mm _____

height 120 mm _____

Cutout

length 270 mm _____

width 270 mm _____

min. ceiling thickness 8 mm _____

max. ceiling thickness 25 mm _____

recessed depth 140 mm _____

¹ RAL code

Installation instructions

