

# JUST 45

CAVO

049-8302539F



Project / Type

Notes

Count / Date



### General

Ceiling , Recessed

tilt max 90°

rotation 360°

gold , RAL 260-M<sup>1</sup>

IP20

640 lm

fixture 96 lm/W<sup>2</sup>

### LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>f(1-5)</sub>: 87

MR 0.59

MDER 0.54

### Optical

flood

beam angle 44°

### Electrical

DALI-2

18 V

system 8.8 W

fixture 6.6 W

400 mA

PC3


### Physical

diameter 45 mm

height 68 mm

0.2 kg


### Light distribution



flood 44°

h (m)	EO <sup>2</sup> (lx)	ø (m)
1	1190	0.82
2	300	1.64
3	130	2.45
4	70	3.27
5	50	4.09

### Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

### Installation instructions

### Lighting calculator

