

SPOT LINE

MOVE IT 25
050-0222538M



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|------------------------------------|--|
| Ceiling / Wall , Track | |
| black , RAL 9005 ¹ | |
| IP20 | |
| 1450 lm | |
| optical inset 96 lm/W ² | |

LED

| | |
|---|--|
| 3000 K | |
| CRI ≥ 97 | |
| L80 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| R _g : 92 , R _f : 86 , R _{f(1-15)} : 94 | |
| MR 0.53 | |
| MDER 0.48 | |

Optical

| | |
|--------------------------|--|
| medium | |
| UGR ≤ 16 | |
| PstLM ≤ 1.0 ³ | |
| SVM ≤ 0.4 ³ | |

Electrical


| | |
|-----------------------|--|
| DALI-2 single control | |
| 48 V | |
| fixture 17.9 W | |
| optical inset 15.2 W | |
| PC3 | |
| 1 DALI Addr. | |

Physical

| | |
|---------------|--|
| length 605 mm | |
| width 25 mm | |
| height 45 mm | |
| 0.39 kg | |

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



SPOT LINE

MOVE IT 25
050-0222538M



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF | 0.98 | 0.93 | 0.89 | 0.85 | 0.81 |
| LSF | 1 | 1 | 1 | 1 | 1 |

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

