

SPOT LINE

MOVE IT 25
050-0222438M



Project / Type	
Notes	
Count / Date	



General

Ceiling / Wall , Track	
black , RAL 9005 ¹	
IP20	
1350 lm	
optical inset 89 lm/W ²	

LED

2700 K	
CRI ≥ 97	
L95 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 101 , R _f : 96 , R _{f-15} : 96	
MR 0.59	
MDER 0.53	

Optical

medium	
UGR < 16	
PstLM ≤ 1.0 ³	
SVM ≤ 0.4 ³	

Electrical


DALI-2 single control	
48 V	
fixture 17.9 W	
fixture 75 lm/W ⁴	
optical inset 15.2 W	
PC3	
1 DALI Addr.	

Physical

length 605 mm	
width 25 mm	
height 45 mm	
0.4 kg	

Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; inserted lenses with medium radiation characteristic 31°; UGR ≤ 16; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

Light distribution



Product drawing



¹ RAL code
² OPTICAL INSET: incl. consideration of optical losses
³ Value of containing product at full load (undimmed)
⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions

