

SPOT LINE

MOVE IT 25

050-0221438M



Project / Type	
Notes	
Count / Date	



General

Ceiling / Wall , Track	
black , RAL 9005 ¹	
IP20	
673 lm	
optical inset 89 lm/W ²	

LED

2700 K	
CRI ≥ 97	
L95 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 101 , R _f : 96 , R _{f-15} : 96	
MR 0.59	
MDER 0.53	

Optical

medium	
UGR < 16	
PstLM ≤ 1.0 ³	
SVM ≤ 0.4 ³	


Electrical

DALI-2 single control	
48 V	
fixture 8.9 W	
fixture 76 lm/W ⁴	
optical inset 7.6 W	
PC3	
1 DALI Addr.	

Physical

length 305 mm	
width 25 mm	
height 45 mm	
0.22 kg	

Light distribution



Product drawing



¹ RAL code
² OPTICAL INSET: incl. consideration of optical losses
³ Value of containing product at full load (undimmed)
⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



SPOT LINE

MOVE IT 25
050-0221438M



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.97	0.96	0.95
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

