

SPOT LINE

MOVE IT 25

050-0220538M



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

black , RAL 9005 ¹

IP20

363 lm

optical inset 96 lm/W²

LED

3000 K

CRI \geq 97

L80 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 92 , R_r: 86 , R₍₁₋₁₅₎: 94

MR 0.53

MDER 0.48

Optical

medium

UGR $<$ 16

PstLM \leq 1.0 ³

SVM \leq 0.4 ³

Electrical

DALI-2 single control

48 V

fixture 4.5 W

fixture 81 lm/W⁴

optical inset 3.8 W

PC3

1 DALI Addr.

Physical

length 155 mm

width 25 mm

height 45 mm

0.12 kg

¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses

³ Value of containing product at full load (undimmed)


⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 97; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; inserted lenses with medium radiation characteristic 31°; UGR \leq 16; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

Light distribution



Product drawing

