

# JUST 55

MOVE IT 25 / 25 S / 45  
050-014243XM



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



### General

Ceiling , Track \_\_\_\_\_

tilt max 90° \_\_\_\_\_

rotation 360° \_\_\_\_\_

special colours \_\_\_\_\_

IP20 \_\_\_\_\_

1680 lm \_\_\_\_\_

### LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 96 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 88 \_\_\_\_\_

MR 0.55 \_\_\_\_\_

MDER 0.5 \_\_\_\_\_

### Optical

medium \_\_\_\_\_

beam angle 23° \_\_\_\_\_

### Electrical

DALI-2 single control \_\_\_\_\_

25.4 W \_\_\_\_\_

PC3 48V \_\_\_\_\_

66 lm/W<sup>1</sup> \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_


### Physical

diameter 55 mm \_\_\_\_\_

height 100 mm \_\_\_\_\_

0.3 kg \_\_\_\_\_


### Light distribution



medium 23°

h (m)	E0° (lx)	ø (m)
1	7740	0.41
2	1930	0.82
3	860	1.22
4	480	1.63
5	310	2.04

### Product drawing



<sup>1</sup> incl. optical losses and the efficiency of the operating device (converter)

### Installation instructions



### Lighting calculator



# JUST 55

MOVE IT 25 / 25 S / 45  
050-014243XM



Project / Type

Notes

Count / Date

## Optical accessories

### HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	50	007-1965598

