

# TULA micro suspended

canopy trim

049-571551XF 005-3521017 002-90732



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Suspended \_\_\_\_\_

special colours \_\_\_\_\_

Canopy traffic white \_\_\_\_\_

IP20 \_\_\_\_\_

798 lm \_\_\_\_\_

fixture 95 lm/W<sup>1</sup> \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 87 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.54 \_\_\_\_\_

## Optical

flood \_\_\_\_\_

beam angle 44° \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrical

non DIM \_\_\_\_\_

220-240 V \_\_\_\_\_

system 11.3 W \_\_\_\_\_

fixture 8.4 W \_\_\_\_\_

18 Vf \_\_\_\_\_

500 mA \_\_\_\_\_

PC2 \_\_\_\_\_

## Physical

diameter 47 mm \_\_\_\_\_

height 500 mm \_\_\_\_\_

0.76 kg \_\_\_\_\_

## Cutout

diameter 65 mm \_\_\_\_\_

min. ceiling thickness 2 mm \_\_\_\_\_

max. ceiling thickness 25 mm \_\_\_\_\_

recessed depth 70 mm \_\_\_\_\_

<sup>1</sup> incl. consideration of optical losses & internal control unit losses

<sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



flood 44°

h (m)	E0° (lx)	ø (m)
1	1480	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Product drawing



## Installation instructions



## Lighting calculator

