

TULA micro suspended

canopy surface

049-571551XF 005-2602197



Project / Type

Notes

Count / Date




Decorative suspended luminaire in aluminium; surface special colours powder coated; pendant fitting with 1500mm suspension; incl. feed (white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC2; 220-240 V; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



flood 44°		
h (m)	EO° (lx)	ø (m)
1	1480	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

Product drawing



General

Ceiling , Suspended

special colours

Canopy traffic white

IP20

798 lm

LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100 , R_f: 90 , R_{f(1-15)}: 87

MR 0.59

MDER 0.54

Optical

flood

beam angle 44°

Electrical

Casambi

220-240 V

system 11.3 W

inset 8.4 W

18 Vf

500 mA

PC2

system 71 lm/W¹

inset 95 lm/W¹

Physical

diameter 47 mm

height 500 mm

0.58 kg

¹ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

