

TULA micro suspended

canopy trim

049-5515517M 005-3521017 002-90733



Project / Type

Notes

Count / Date



220-240V

No sun

UGR

≤ 10

cd/m²

≤ 1500

CRI

≥ 90

X-PERT

General

Ceiling , Suspended

white , RAL9016 ¹

Canopy traffic white

IP20

746 lm

LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100 , R_f: 90 , R_(f-15): 87

MR 0.59

MDER 0.54

Optical

medium

beam angle 25°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

11.3 W

inset 8.4 W

500 mA

PC2 220-240V

66 lm/W

Physical

diameter 47 mm

height 300 mm

0.57 kg

Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 130 mm

¹ RAL code ² Value of containing product at full load (undimmed)



Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	3230	0.44
2	810	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Product drawing



Installation instructions



Lighting calculator

