

# TULA nano suspended

canopy surface

049-5510418M 005-2602138



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface black powder coated; pendant fitting with 1500mm suspension; incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

## Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	2620	0.44
2	660	0.89
3	290	1.33
4	160	1.77
5	100	2.22

## Product drawing



### General

Ceiling , Suspended

black , RAL9005 <sup>1</sup>

Canopy jet black

IP20

699 lm

### LED

2700 K

CRI  $\geq 90$

initial MacAdam  $\leq 3$  SDCM

### Optical

medium

beam angle 25°

### Electrical

DALI-2

12.0 W

inset 9.0 W

18 Vf

500 mA

PC2 220-240V

58 lm/W

### Physical

diameter 26 mm

height 300 mm

0.29 kg

<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator

