

ARY adjustable rod suspended

canopy trim

049-5231418F 005-3521018 002-90732



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

tilt max 90°

rotation 265°

black , RAL9005 ¹

Canopy jet black

IP20

688 lm

LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-5)}: 89

MR 0.54

MDER 0.49

Optical

flood

beam angle 44°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

system 11.2 W

inset 8.4 W

18 Vf

500 mA

PC2 220-240V

system 61 lm/W³

inset 82 lm/W⁴

Physical

rod 1500 mm with hook

diameter 47 mm

height 110 mm

0.67 kg

Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm


recessed depth 70 mm

¹ RAL code ² Value of containing product at full load (undimmed)

³ incl. optical losses and the efficiency of the operating device (converter)

⁴ incl. optical losses

Light distribution



flood 44°

h (m)	E0° (lx)	ø (m)
1	1280	0.82
2	320	1.64
3	140	2.45
4	80	3.27
5	50	4.09

Product drawing



Installation instructions

Lighting calculator

