

TULA nano suspended

canopy surface

049-5710518F 005-2602118



Project / Type _____

Notes _____

Count / Date _____



Decorative suspended luminaire in aluminium; surface black powder coated; pendant fitting with 1500mm suspension; incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



flood 30°

h (m)	EO° (lx)	ø (m)
1	2110	0.53
2	530	1.07
3	230	1.60
4	130	2.13
5	80	2.66

Product drawing



General

Ceiling , Suspended _____

black , RAL9005 ¹ _____

Canopy jet black _____

IP20 _____

717 lm _____

LED

3000 K _____

CRI ≥ 90 _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

flood _____

beam angle 30° _____

Electrical

non DIM _____

system 12.1 W _____

inset 9.1 W _____

18 Vf _____

500 mA _____

PC2 220-240V _____

system 59 lm/W² _____

inset 79 lm/W³ _____

Physical

diameter 26 mm _____

height 500 mm _____

0.41 kg _____

¹ RAL code

² incl. optical losses and the efficiency of the operating device (converter)

³ incl. optical losses

Installation instructions



Lighting calculator

