

TULA micro suspended

canopy trim

049-5515414M 005-3521018 002-90733



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

chrome

Canopy jet black

IP20

648 lm

fixture 77 lm/W¹

LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89

MR 0.54

MDER 0.49

Optical

medium

beam angle 25°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

220-240 V

system 11.3 W

fixture 8.4 W

18 Vf

500 mA

PC2

Physical

diameter 47 mm

height 300 mm

0.57 kg

Cutout

diameter 65 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 130 mm

¹ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
² Value of containing product at full load (undimmed)


Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	2800	0.44
2	700	0.89
3	310	1.33
4	180	1.78
5	110	2.22

Product drawing



Installation instructions



Lighting calculator

