

# ARY adjustable rod suspended

canopy trim

049-523161XF 005-3521017 002-90732



Project / Type

Notes

Count / Date



### General

Ceiling , Suspended

tilt max 90°

rotation 265°

special colours

Canopy traffic white

IP20

791 lm

### LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 89 , R<sub>t</sub>(1-5): 87

MR 0.81

MDER 0.73

### Optical

flood

beam angle 44°

PstLM ≤ 1.0<sup>1</sup>

SVM ≤ 0.4<sup>1</sup>

### Electrical

non DIM

system 11.2 W

inset 8.4 W

18 Vf

500 mA

PC2 220-240V

system 71 lm/W<sup>2</sup>

inset 94 lm/W<sup>3</sup>

### Physical

rod 1500 mm with hook

diameter 47 mm

height 110 mm

0.68 kg

### Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 70 mm

<sup>1</sup> Value of containing product at full load (undimmed)

<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)

<sup>3</sup> incl. optical losses

### Light distribution



flood 44°

h (m)	E0° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

### Product drawing



### Installation instructions



### Lighting calculator

