

ARY adjustable rod suspended canopy surface

049-5231518M 005-2602118



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended
 tilt max 90°
 rotation 265°
 black , RAL 9005 ¹
 Canopy jet black
 IP20
 739 lm
 fixture 88 lm/W²

LED

3000 K
 CRI ≥ 90
 L90 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 100 , R_f: 90 , R_{1-15}: 87
 MR 0.59
 MDER 0.54

Optical

medium
 beam angle 25°

Electrical

non DIM
 220-240 V
 system 11.2 W
 fixture 8.4 W
 18 Vf
 500 mA
 PC2

Physical


rod 1500 mm with hook
 diameter 47 mm
 height 110 mm
 0.66 kg

¹ RAL code

² incl. consideration of optical losses & internal control unit losses

Decorative suspended luminaire in aluminium; surface black powder coated; height adjustable U-profile pendant rod suspension (black) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; spotlight head 265° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2; 220-240 V; light source not replaceable; control gear replaceable by an authorized professional;


Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Product drawing



Installation instructions



Lighting calculator

